

Cobblersidge



Construction	Textured Hi-Low Loop Pile Carpet
Yarn	100% Stainproof Miracle Fibre
Width	4.0m
Standard Roll Length	35m
Yarn Weight	30oz/yd ²
Pile Height	6.0mm
Total Thickness	8.5mm
Machine Gauge	5/32"
Primary Backing	Woven Polypropylene
Secondary Backing	FusionBac
Electrical Properties	Antistatic
Electrical Propensity	< 2kV (EN 1815 / ISO 6356)
VOC Rating	Pass (GBCSA/GLP Criteria)
Anti-allergenic Properties	Will not shed or pill. Resistant to mould & mildew.
Underfloor Heating	Suitable - Maximum Temperature 37°C
Rating	Heavy Duty Residential
Stair Rating	Suitable
Warranties	10 Year Residential Warranty
Installation	All seams must be sealed. Must be laid in accordance with AS/NZ Installation Standards.
Environmental	Greenstar Low VOC, solution dyeing uses no water, Eco-Wash™ Treatment Occupational Health and Safety Management ISO 45001 Environmental Management ISO 14001 Quality Management ISO 9001



- For samples, range and warranty details please contact us on +61 7 5415 1134 or belgotex.com.au
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

Belgotex®

A world of perfect choices_