Sumptuous











| Construction | Tufted Cut Pile Carpet |
|------------------------------|--|
| Yarn | 100% Premium Soft Solution Dyed Nylon |
| Width | 4.0m |
| Standard Roll Length | 25m |
| Yarn Weight | 46oz/yd² |
| Pile Height | 10.0mm |
| Total Thickness | 12.0mm |
| Machine Gauge | 1/10th |
| Primary Backing | Woven Polypropylene |
| Secondary Backing | FusionBac |
| Electrical Properties | Antistatic |
| Electrical Propensity | < 2kV (EN 1815 / ISO 6356) |
| Fire Rating | CRF 4.5kW/m² (ISO 9239-1) |
| VOC Rating | Pass (GBCSA/GLP Criteria) |
| Anti-allergenic Properties | Will not shed or pill. Resistant to mould & mildew. |
| Underfloor Heating | Suitable - Maximum Temperature 37°C |
| Rating | Extra Heavy Duty Residential Medium Duty Commercial |
| Stair Rating | Suitable |
| Warranties | 15 Year Residential Warranty 7 Year Commercial Warranty |
| Installation | All seams must be sealed. Must be laid in accordance with AS/NZ Installation Standards. |
| Environmental | Greentag Certified Greenstar Low VOC, solution dying uses no water, Eco-Wash™ Treatment Occupational Health and Safety Management ISO 45001 Environmental Management ISO 14001 Quality Management ISO 9001 |





- For samples, range and warranty details please contact us on +61 7 5415 1134 or belgotex.com.au
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

Belgotex[®]

A world of perfect choices_

belgotex.com.au 27/02/2024