


# Technical Specification

## Hybrid Herringbone Collection



Attributes	Standard	Result
Type of floor covering		Hybrid / Rigid core
Installation		Unilin Click System
Core		SPC
Colours		5
Size		650mm x 127mm
Thickness		9.0mm
Core thickness		7.0mm
Wear layer		0.5mm
Surface Features		Embossed
Backing		2mm Acoustic underlay
Packaging		18 Planks / pack = 1.486m <sup>2</sup>
Total weight		8.75kg/m <sup>2</sup> / 17.5kg per pack
Beveled edge		Micro Bevel Edges
Classification	ISO 10874 / EN 685 ISO 10874 / EN 685	Commercial: light Domestic: heavy
Reaction to fire	AS/NZ ISO9239 1-2003	CHF: ≥10.05kW/m <sup>2</sup> Smoke value: 132%.min
Slip resistance	AS 4586:2013 Appendix A	P3
Dimensional stability	Heat at 60°C for 24 hours	Length: -0.8% Width: -0.09%
Acoustic impact noise reduction	AS/NZ ISO 717.2-2004	FIIC <sup>4,5</sup> = 61 L'nTw <sup>3</sup> = 41 AAAC 5 Star Rating <sup>1</sup>
Underfloor heating		Suitable for hydronic underfloor heating, max. 27°C
VOC Emissions	ASTM D5116-17 Green Building Council of Australia Phthalate Free	Compliant for VOC  Yes
Quartz content (wt%)		Not detected
Warranty	Commercial Domestic	10 Years warranty* 25 Years warranty*

### Create Timber Floor

18 Natalia Ave, Oakleigh South VIC 3167 | 03 9558 6191 | [info@createtimberfloor.com.au](mailto:info@createtimberfloor.com.au) | [www.createtimberfloor.com.au](http://www.createtimberfloor.com.au)